


ABMESSUNGEN

für Schrauben von	d min.-max.	D max.	b min.-max.	s min.-max.	h Resthöhe	kg/1.000 Stück	Verpackungseinheit
21 "FE21 SK"	21,00-22,50	42,90	9,80-10,20	5,80-6,20	16,80	84	300
24	23,40-24,60	45,00	9,80-10,20	5,80-6,20	17,80	88	300
24 "7/8"	24,00-25,20	45,20	9,80-10,20	5,80-6,20	17,80	88	300
25 "FE6"	25,00-26,20	46,60	9,80-10,20	5,80-6,20	17,80	92	300
26	25,40-26,60	47,00	9,80-10,20	5,80-6,20	17,80	92	300
26	25,70-27,50	47,50	9,80-10,20	5,80-6,20	17,80	92	200
28 "FE15"	28,00-29,20	53,60	11,80-12,20	5,80-6,20	17,80	122	200
dreifach "FE19"							
26	25,40-26,60	47,00	9,80-10,20	5,80-6,20	-	145	-

Härte / Hardness: 430-490 Hv

 roh gefettet / oiled
 mechanisch verzinkt / mechanical zinc plated
 Zinklamelle / zincflake
 feuerverzinkt / hot dip galvanized
 andere Oberflächen Ausführungen auf Anfrage

Bestimmte Abmessungen sind mit partieller Prägung erhältlich.
Certain dimensions are available with partiell teeth on the surface.